

HPE Connected Backup

Product Overview

Version 8.8.5
19 November 2015

Protect



Hewlett Packard
Enterprise

Legal Notices

Warranty

The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HPE shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

Restricted Rights Legend

Confidential computer software. Valid license from HPE required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright Notice

© Copyright 2015 Hewlett Packard Enterprise Development LP

Trademark Notices

Microsoft is a registered trademark, and MS-DOS, Windows, Windows 95, Windows NT, SharePoint, and other Microsoft products referenced herein are trademarks of Microsoft Corporation.

UNIX is a registered trademark of The Open Group.

AvantGo is a trademark of AvantGo, Inc.

Epicentric Foundation Server is a trademark of Epicentric, Inc.

Documentum and eRoom are trademarks of Documentum, a division of EMC Corp.

FileNet is a trademark of FileNet Corporation.

Lotus Notes is a trademark of Lotus Development Corporation.

mySAP Enterprise Portal is a trademark of SAP AG.

Oracle is a trademark of Oracle Corporation.

Adobe is a trademark of Adobe Systems Incorporated.

Novell is a trademark of Novell, Inc.

Stellent is a trademark of Stellent, Inc.

All other trademarks are the property of their respective owners.

Acknowledgements

RSA Data Security, Inc. MD5 Message-Digest Algorithm; zlib general purpose compression library, Jean-loup Gailly and Mark Adler; Info-ZIP, more information at <ftp://ftp.info-zip.org/pub/infozip/license.html>; HTML-to-RTF Pro DLL 1.8 © 2002-2007 SautinSoft.

Chapter 2

Product Architecture 21

- Product Components 22
- Agents 24
 - File Selection 24
 - File Compression and Encryption 25
 - File Transmission 25
- Data Center 25
 - Data Center Servers 25
 - Data Center Databases 26
 - Data Center Configurations 27
 - Stand-alone Configurations 27
 - Mirrored Configurations 28
 - Clustered Configurations 31
 - Data Center Management Console 33
- Archive 33
 - Life Cycle of an Archive 34
 - Sizing and Splitting Archive 34
- Support Center 35
- Account Management Website 35
- MyRoam 36

Chapter 3

Management Applications and Utilities 37

- Compactor 37
- DataBundler 38
- Data Center Utilities 39
- Data Center Toolkit 39

Chapter 4

Connected Backup Processes 41

- File Backup 41
- File Retrieval 43
- File Management 44
 - Base and Delta Files 44
 - Expiration Dates 44
 - Rebasing 44
- Compaction 45

Chapter 5

Connected Backup Deployment 47

- Deploy the Data Center 47
 - Prepare Your Environment 48
 - Install and Enable MyRoam 49
 - Gather Information that You Need to Provide During Installation 49
 - Install the Data Center Software 49
 - Back Up Certificate Files 49
 - Verify the Data Center Installation 49
- Install Support Center and Account Management Website 50
- Use Support Center to Create Agent Communities 50
- Use Support Center to Create Agent Configurations 51
- Create Agent Rule Sets 52
- Deploy the Account Management Website 52
- Deploy Agents 52

Index 55

About This Document

This manual provides an introduction to the HPE Connected Backup features, components, architecture, and deployment options.

This manual is intended for administrators and technicians who deploy, manage, and use the Connected Backup products.

- [Documentation Updates](#)
- [Related Documentation](#)
- [Conventions](#)
- [Product References](#)
- [Customer Support](#)

Documentation Updates

The information in this document is current as of HPE Connected Backup version 8.8.5. The content was last modified 19 November 2015.

You can retrieve the most current product documentation from the Hewlett Packard Enterprise Knowledge Base on the Customer Support Site.

A document in the Knowledge Base displays a *version number* in its name, such as *IDOL Server 7.5 Administration Guide*. The version number applies to the product that the document describes. The document may also have a *revision number* in its name, such as *IDOL Server 7.5 Administration Guide Revision 6*. The revision number applies to the document and indicates that there were revisions to the document since its original release.

Hewlett Packard Enterprise recommends that you periodically check the Knowledge Base for revisions to documents for the products your enterprise is using.

To access the documentation

1. Go to the Customer Support site:
<https://customers.autonomy.com>
2. Click **Login**.
3. Type the login credentials that you were given, and then click **Login**.
The Customer Support Site opens.
4. Click **Knowledge Base**.
The Knowledge Base Search page opens.
5. Search or browse the Knowledge Base.
To search the knowledge base:
 - a. In the Search box, type a search term or phrase and click **Search**.
Documents that match the query display in a results list.To browse the knowledge base:
 - a. Select one or more of the categories in the **Browse** list. You can browse by:
 - **Repository**. Filters the list by Documentation produced by technical publications, or Solutions to Technical Support cases.
 - **Product**. Filters the list by product. For example, you could retrieve documents related to IDOL Server, Virage Videologger, or KeyView Filter.
 - **Version**. Filters the list by product or component version number.
 - **Type**. Filters the list by document type. For example, you could retrieve Guides, Help, Packages (ZIP files), or Release Notes.
 - **Format**. Filters the list by document format. For example, you could retrieve documents in PDF or HTML format. Guides are typically provided in both PDF and HTML format.
6. To open a document, click its title in the results list.
To download a PDF version of a guide, open the PDF version, click the Download icon  in the PDF reader, and save the PDF to another location.
To download a documentation ZIP package, click Get Documentation Package under the document title in the results list. Alternatively, browse to the desired ZIP package by selecting either the Packages document Type or the ZIP document Format from the Browse list.

To send feedback on documentation

- send email to AutonomyTPFeedback@hpe.com
- provide:
 - full document title with version and revision number
 - location: heading, a snippet of text or screen capture
 - your comments
 - your contact information in the event we need clarification

Related Documentation

The following documents provide more details on Connected Backup:

- *Connected Backup Release Notes*
- *Connected Backup Product Overview*
- *Connected Backup Installing PC Agents*
- *Connected Backup Installing Mac Agents*
- *Connected Backup Administering PC Agents*
- *Connected Backup Administering Mac Agents*
- *Connected Backup Installing the Data Center*
- *Connected Backup Administering the Data Center*
- *Connected Backup Upgrading the Data Center*
- *Connected Backup Data Center Disaster Recovery*
- *Connected Backup Data Transfer API Administration Guide*
- *Connected Backup Management API Administration Guide*
- *Connected Backup Account Management Web Services Development*
- *Connected Backup Web Services Programming Reference*
- *Connected Backup PC Agent Quick Start*
- *Connected Backup Mac Agent Quick Start*
- *Connected Backup Media Agent Quick Start*
- *Connected Backup Agent Version Matrix*

- *Connected Backup Interoperability Matrix*
- *Connected Backup Requirements Matrix*
- *Connected Backup Application Localization Matrix*
- *Connected Backup Documentation Localization Matrix*

In addition, all Connected Backup applications include online help.

Conventions

The following conventions are used in this document.

Notational Conventions

This document uses the following conventions.

Convention	Usage
Bold	User-interface elements such as a menu item or button. For example: Click Cancel to halt the operation.
<i>Italics</i>	Document titles and new terms. For example: <ul style="list-style-type: none"> ■ For more information, see the <i>IDOL Server Administration Guide</i>. ■ An <i>action command</i> is a request, such as a query or indexing instruction, sent to IDOL Server.
<code>monospace font</code>	File names, paths, and code. For example: The <code>FileSystemConnector.cfg</code> file is installed in <code>C:\Program Files\FileSystemConnector\</code> .
monospace bold	Data typed by the user. For example: <ul style="list-style-type: none"> ■ Type run at the command prompt. ■ In the User Name field, type Admin.
<code>monospace italics</code>	Replaceable strings in file paths and code. For example: <code>user <i>UserName</i></code>

Notices

This document uses the following notices:



CAUTION A caution indicates an action can result in the loss of data.



IMPORTANT An important note provides information that is essential to completing a task.



NOTE A note provides information that emphasizes or supplements important points of the main text. A note supplies information that may apply only in special cases—for example, memory limitations, equipment configurations, or details that apply to specific versions of the software.



TIP A tip provides additional information that makes a task easier or more productive.

Product References

This document references the following product:

- HPE Connected Backup

CHAPTER 1

Products and Features

This chapter describes the Connected Backup products and their key features.

- [Connected Backup Products](#)
- [Key Features](#)

Connected Backup Products

Connected Backup is software that backs up files on users' computers and stores the backed up files in a centralized location. If users lose files on their computers, they can retrieve the lost files from the stored backups.

You can purchase the following types of Connected Backup products:

- A licensed product for users who manage their data storage facility.
- A subscription service for users who back up files to a storage facility that another company manages

You can purchase the following Connected Backup solutions:

- Connected Backup for Mac
- Connected Backup for PC

Licensed Product

Customers who have the licensed product install file storage software on their hardware, install software on users' computers, and use a Web-based application to manage accounts for the computers that host Connected Backup software.

If you use the licensed Connected Backup product, refer to the following documentation:

- *Installing the Data Center*
- *Administering the Data Center*
- *Installing Agents* for your operating system
- *Administering Agents* for your operating system
- *Account Management Web Services Development*

Subscription Service

Customers who subscribe to the Connected Backup service use a storage system that a third party manages. They do not install the storage facility software. However, they install software on users' computers and use a Web-based application to manage accounts for the computers that host Connected Backup software.

If you use the subscription service, refer to *Installing Agents* for your operating system and *Administering Agents* for your operating system.

Key Features

The following topics describes the key features of the Connected Backup product.

Reliable Data Backup

Connected Backup uses software, the Agent, that you install on client computers and a centralized storage system, the Data Center, to back up files, operating systems, and applications.

A graphic interface on users' computers lets users review the set of files that they or an administrator specify for backup. If the Agent settings allow, users can edit the files in their backup set.

Administrators can configure the product so that backups start on a scheduled basis. Alternatively, users can initiate backups.

Connected Backup includes Agents for Mac, and Agents for PC.

For more information about how the Agent backs up files to the Data Center, see [“File Backup” on page 41](#). Also refer to *Administering Agents* for your operating system.

File Retrieval

Users can retrieve one or more backed-up files and restore lost or corrupted files to their computers. Users can retrieve files from the Agent graphic interface or a command-line interface.

For more information about how the Agent retrieves files from the Data Center, see [“File Retrieval” on page 43](#). Also refer to *Administering Agents* for your operating system.

32-bit and 64-bit Support

You can install the Connected Backup Agent on computers with a 32-bit platform or a 64-bit platform. The installation process is the same regardless of the platform.

You can retrieve backed up files across bit platforms. For example, you can retrieve files from a computer that has a 32-bit platform to a computer that has a 64-bit platform.

Administrators can also create or upgrade a Connected Backup Data Center using 32-bit or 64-bit Windows platforms.

Deployment Options

To enable the Agent to back up files on a computer, you must deploy the Agent on each computer from which you want to back up files. Connected Backup offers several ways to deploy the software. For more information, see [“Deploy Agents” on page 52](#). Also refer to *Installing Agents* for your operating system.

Support for Wise Transform

You can use the Wise Transform tool instead of the Connected Backup command-line interface to set parameters in the Agent installation file that you deploy to users' computers. For information about how to use transforms, refer to *Installing PC Agents*.

Agents for Disk Images

You can install an Agent that does not back up files until a user or administrator activates it. Install this type of Agent when you do not want the Agent to back up files on the installation computer, but you want to include it in a disk image of a

computer system that you want to clone to other computers. After users receive a computer that has this Agent, users or a script must activate and register the Agent.

For more information about Agents for disk images, refer to *Installing Agents* for your operating system.

Digitally Signed Agent Installation Programs

You can use certificates that you obtain from a trusted certificate authority to digitally sign the Agent Setup file. When you sign the Agent Setup file, users who install the Agent receive a message at the start of the installation process to ensure them that the file comes from a trustworthy source. For more information, refer to Support Center Help.

A Graphic Interface for Setting Up Agents on Client Computers

The Agent Startup Wizard is a graphic interface that, if enabled, helps you configure and register new Agent accounts and recover accounts. The Agent Startup Wizard opens when you start the Agent Setup program for the first time.

For more information about the Agent Startup Wizard, refer to *Installing Agents* for your operating system.

An Efficient Way to Upgrade Agents

You can use the Central Administration feature to upgrade Connected Backup Agents on client computers to a new version the next time that they connect to the Data Center. When an Agent connects to the Data Center, the Data Center downloads and installs the new Agent version. For more information, refer to *Installing Agents* for your operating system. Also refer to Support Center Help.

Branding Options

The branding feature lets you customize the Connected Backup product to use your company logo. For information about the components that you can brand, refer to *Administering Agents* for your operating system. For instructions on how to brand the product, refer to Support Center Help.

Options to Efficiently Back Up E-Mail for PC Agent Accounts

The Connected Backup solution provides the following ways to back up Microsoft Outlook Personal Folder files (*.pst files) and Lotus Notes database files (*.nsf files):

FDCC Compliance

As of version 8.4, Connected Backup complies with Federal Desktop Core Configuration (FDCC) 1.2 requirements.



NOTE As per the FDCC 1.1/1.2 release, Group Policy Settings do not need to change to run Connected Backup components in FDCC-enabled environments.

For more information about preinstallation requirements for Support Center access in an FDCC environment, refer to *Administering Agents* for your operating system.

CHAPTER 2

Product Architecture

This chapter describes the components that comprise the Connected Backup product and how they work together to back up and retrieve files. It also describes the configuration types that you can deploy.

- [Product Components](#)
- [Agents](#)
- [Data Center](#)
- [Archive](#)
- [Support Center](#)
- [Account Management Website](#)
- [MyRoam](#)

Product Components

Connected Backup consists of the following major components:

Agents	<p>The application that runs on client computers and communicates with the Data Center to back up and retrieve files. The Agent service runs in the background to perform backups. The Agent user interface lets users start backups manually, retrieve files, and view the backup history. For more information about the Agent user interface, refer to the Agent Help.</p> <p>Each client computer that hosts an Agent has one account with the Data Center.</p>
Data Center	<p>The hardware (one or more servers) and software that stores and manages backed-up files. The Data Center supports the following types of Agents:</p> <ul style="list-style-type: none">PC AgentsMac AgentsLegacy PC Agents (version 7.x) <p>The Data Center Management Console is the graphic interface that lets you manage the Data Center.</p> <p>For more information about the Data Center, see “Data Center Databases” on page 26.</p>
Connected Backup databases	<p>Databases that the Data Center uses to store backed up data and information about Agent accounts.</p>
Storage devices	<p>Devices that are part of a Data Center that is configured to store files from the Data Center disks to another device.</p>

Agents

The Agent is software on users' computers that contacts the Data Center to back up and retrieve files.

The Connected Backup software supports the following types of Agents:

- PC Agents that run on Windows PC operating systems
- Mac Agents that run on Apple Macintosh operating systems

Each computer that hosts an Agent has an account in the Data Center. If your computer fails, or if you get a new computer, you can transfer the data associated with your account (such as backup settings and existing backups) to a different computer. An account can exist on only one computer at a time.

Agents perform the following actions:

- Specifies files on the user's computer to back up
- Compresses and encrypts files
- Sends files to the Data Center

Agents initiate all activity with the Data Center. The Data Center does not contact the Agent.

File Selection

The Agent uses rules to determine the location and types of files to select for backup. When a backup session begins, the Agent scans the files selected for backup. If a file is new or modified, the Agent backs it up. For more information about how the Agent uses rules to select files for backup, refer to the Agent Help for your operating system.

After the Agent scans a computer's hard drives for files that are eligible for backup, it contacts the Data Center to initiate a backup session. The Agent also prepares files for backup and notifies the Data Center if you deleted previously backed-up after the last backup session. To retrieve files, the Agent lets you issue requests to the Data Center and download the files.

After the Agent scans the computer's hard drive, the Agent determines which files to back up and processes the files for transmission to the Data Center. For the first system backup, the Agent sends entire files to establish a base for each file. For subsequent backups, it sends only the changes to the file since the last good backup. This change is called a delta.

Data Center Databases

When you install the Data Center software, it creates the SQL databases that it uses to store information about files.

The following table describes each database and how the Data Center uses it:

Database	Description
Registry database	<p>The Data Center uses the Registry database to perform the following tasks:</p> <ul style="list-style-type: none"> ■ Record account activity (for example, the creation of new Agent accounts or changes to account information). ■ Generate reports within Support Center. ■ Store user information. ■ In mirrored configurations, obtain information about the mirror. For information about mirrored configurations, see “Mirrored Configurations” on page 28.
Directory database	<p>The Data Center uses the Directory database to store the following information:</p> <ul style="list-style-type: none"> ■ Archives. ■ User files in a given archive. ■ Locations of each archive on disk or on an archive storage device. ■ Information about replication and Compactor. For information about Compactor, see “Compactor” on page 37. <p>The Data Center uses this database when a user tries to retrieve data.</p>


If you host your Data Center and you run it as a stand-alone server, the Data Center backs up the databases during the automatic daily and weekly maintenance. If a disaster occurs, you can use the backed-up database files and transaction logs to reconstruct the Data Center. For more information about these procedures, refer to *Administering the Data Center*.

If you host your own Data Center and you run it on a mirrored or clustered configuration, you can rebuild the databases from the mirror. For more information about the procedures that you can use to rebuild the databases, refer to *Data Center Disaster Recovery*.

During the course of daily activity, the Data Center replicates database tables between the mirrored servers. Several tables store information that is unique to each server. The Data Center also replicates these tables. For example, the Data Center replicates the ArchiveeClip table on Server A to a table named MirrorArchiveeClip on Server B. If Server A database fails, you can copy the

If the Data Center server is unavailable (for example, during maintenance), the Agent must wait for it to become available before the Agent can back up or retrieve files. In a mirrored configuration, if one server is unavailable, the Agent connects to the mirror server. In a mirrored environment, users remain unaware of server downtime.

The following figure shows a stand-alone configuration that uses an attached archive storage device:




Mirrored Configurations

Mirrored configurations use two identical Data Centers, ideally at physically separate sites. Each Data Center uses the same software, stores the same data, and services the same Agent communities. The two mirrored servers are redundant peers. Neither server is dominant over the other. Each server can perform any backup or retrieval operation.

When a Data Center server creates a new user account, the Agent assigns one of the mirrored Data Center servers as the primary Data Center for the account. An Agent typically contacts its primary Data Center. If the primary Data Center is unavailable, the Agent contacts the mirror instead. The alternating assignment of

The following figure shows a mirrored server configuration:



The figure depicts a configuration that uses the highest level of data protection — a mirrored Redundant Array of Independent (or Inexpensive) Disks (RAID) with an attached storage device. Each side of the mirror is in a different location. Although the figure shows Agents for only the Primary Data Center, an equal number of Agents use the Secondary Data Center as their Primary Data Center. Both Data Center servers process requests over the network for new accounts and accept Agent backup and retrieval requests.


Clustered Configurations

For Data Centers that serve a large number of users or receive a large amount of data, a mirrored configuration might not have sufficient capacity to handle the backup and retrieval activity. In this situation, you might want to set up clusters at each Data Center site.

To balance loads, clustered Data Centers distribute backup and retrieval requests to more than one pair of mirrored servers. The mirrored servers in the cluster provide load balancing, redundant storage of data, and fail-safe availability of file backup and retrieval services.

Clustered configurations have two or more pairs of Data Center servers. Each server in a pair resides on a Data Center at a different location. Each mirrored pair of Data Center servers provides backup services to a subset of the user community and failover for each other. The group of Data Center servers is a **cluster**. The Data Center servers in the cluster share the same Registry database in SQL, but each mirrored pair of servers has its own Directory database.

The following figure shows Data Center servers A1 and B1, which form a mirrored pair, with archive storage devices for extended storage of backed up data:



In this configuration, the Data Center servers A1 and B1 share the same set of users and maintain identical Directory databases. The same is true for Data Center servers A2 and B2, which are mirrors of each other. Servers A1 and B1 serve a subset of their user community, while servers A2 and B2 serve the other half. Servers A2 and B2 use the Registry databases that reside on A1 and B1 respectively.

The following table describes the basic elements in an archive:

Element	Description
Archive header	The archive header contains information about the archive file. This information includes the name of the file, the account from which the data originated, and the current version of the Agent in use when the Data Center created the archive.
File header	The file header or headers contain detailed information about the files in the archive. It identifies whether the file is a baseline or delta, the current revision level (if it is a delta), and its path and file names. When you delete a file from the client or exclude a file from the backup list, the Agent transmits just a file header that signals to the Data Center that the user deleted or excluded the file.
File data	The file data in an archive consists of the files in their compressed and encrypted form.

Life Cycle of an Archive

The life cycle of an archive depends on the configuration of the Data Center where it resides. From the first transmission of account data to the Data Center, the life cycle of an archive proceeds as follows:

1. The Data Center BackupServer service distributes the client data into one or more archives on the volume that has the greatest amount of available disk space.
2. The Data Center IndexServer service indexes the archives and their individual contents in the Directory database to track each revision of each backed up file.
3. In mirrored or clustered Data Centers, the ReplicationServer service replicates the archives to the mirror (if applicable).
4. The Compactor service routinely checks each account's archives for expired revisions. It then freshens (repackages) the archives as needed.

For more information about the Data Center services that archive, index, and replicate data, refer to *Administering the Data Center*.

Sizing and Splitting Archive

When an Agent transmits account backup data to the Data Center, the BackupServer service groups it into archives. During this process, BackupServer regulates the size of the archives and creates new archives for the client data. The BackupServer creates a new archive under the following conditions:

- The archive reaches 90 MB in size.
- The number of files in the archive totals 2,000.

- The next file to come from the client is greater than 225 MB.

The BackupServer service creates a new archive as needed to efficiently group the data into the smallest possible units. For example, files A, B, and C together represent 40 MB, but file D equals 60 MB, then BackupServer combines A, B, and C together in one archive and creates a new archive for file D.

Archives can include information from many individual files. Baselines of new files (that is, backup information for a file's first backup) and deltas of older files (that is, backup information for a file previously backed up) can reside together in the same archive. However, backup information for a single file exists in multiple archives. This is because new archives of account data are created during every backup session. For example, a large file of 10 MB that undergoes significant revisions between each of five backup sessions have its backups stored in five archives. The first time the Agent backs up a file to the Data Center, the Data Center writes a baseline of the file to one archive. For the four subsequent revisions, the Data Center writes each file deltas to four additional archives.



NOTE The data in a single archive comes from one backup session from a single account.

For more information, see [“File Management” on page 44](#).

Support Center

Support Center is a Web-based management application that lets you create and manage Agent configurations and registered accounts. For information about how to use Support Center, refer to Support Center Help and *Administering Agents* for your operating system.

Account Management Website

The Account Management Website is a Web-based application that lets users perform the following tasks:

- Register a new account and download the Agent software.
- View account information.
- Modify profile information such as e-mail address and password.

- Recover an account.
- Use the MyRoam application to retrieve files.
- For PC Agents, order images of backed-up files on different types of media. You cannot use media images with Mac Agents.

To access to the Account Management Website, you can enter the URL to the Website in a Web browser, or select a link in the Agent user interface. The URL for the Account Management Website is case-sensitive. Technicians can select a link in Support Center to gain access to users' account information on the Account Management Website. When technicians gain access to accounts in this manner, they can gain access to only the features and information available to the user.

MyRoam

The MyRoam application is an optional, Web-based application that lets users retrieve backed-up files using a Web browser instead of the Agent user interface. The MyRoam application runs on the same secure Web server as the Account Management Website.

To gain access to the MyRoam application, users must log on to the Account Management Website.

CHAPTER 3

Management Applications and Utilities

This chapter describes the Connected Backup applications and utilities that you can use to manage files.

- [Compactor](#)
- [DataBundler](#)
- [Data Center Utilities](#)
- [Data Center Toolkit](#)

Compactor

Compactor is a Data Center service that removes data from the Data Center. Using the Compactor service is beneficial for the following reasons:

- Reduces overall storage requirement for the Data Center.
- Improves Agent file retrieval performance.
- Reduces the size of the databases.
- Improves data integrity.

Compactor runs on all Data Center configurations. However, it runs differently on a stand-alone server than it does in a mirrored configuration.

The following table describes how Compactor runs on each type of Data Center server configuration:

Data Center Configuration Type	How Compactor runs
Stand-alone	Runs on one server.
Mirrored	Runs on two servers. However, only the primary server controls the workload of the compaction process.
Clustered	Runs on one primary server for every mirrored pair in the cluster. For example, a clustered Data Center with three mirrored pairs has three primary servers. You can check the status of the primary server(s) in the Compactor view of DCMC. For instructions, see DCMC Help.

For information about the compaction process, see [“Compaction” on page 45](#).

DataBundler

The DataBundler application creates images that contain backed-up data for individual PC Agent accounts. If you are a licensed customer, you use your own software and hardware to burn the DataBundler images onto a CD or DVD. If you are a subscription customer, you request the images on CD or DVD from the organization that manages your Data Centers.

Users can recover Agent accounts or retrieve files from the images that DataBundler creates. Images are useful when you need to retrieve files but a client system is unable to connect to a Data Center, or if you need to retrieve a large number of files and the client system uses a slow connection to the Data Center. You cannot use Mac Agents to retrieve files from images.

When the DataBundler application receives a request for an account image, it interacts with the Data Center to gather all files for a selected account and assemble them into a compressed account image. The account image includes a copy of the Agent, enabling users to recover their accounts or retrieve some or all files through the familiar Agent user interface. The DataBundler application also creates shipping and disk labels you can print using your own software and hardware.

Technicians use Support Center to request an image on media for PC Agents. Users open the Account Management Website to request images on media.

CHAPTER 4

Connected Backup Processes

This chapter describes the processes that Connected Backup uses to back up, retrieve, restore, and manage files.

- File Backup
- File Retrieval
- File Management
- Compaction

File Backup


The Agent backs up new files and files that have changed since your previous backup. When the Agent backs up the changed files, it backs up only the changed portions of the files. When the Agent sends files to the Data Center, the Data Center compares the files to those backed up by other users. Duplicate files are not sent to the Data Center, using SendOnce technology.

You can use the Agent to review the set of files specified for backup and, if your Agent settings allow, edit the files in your backup set.

You can configure the Agent so that backups start on a scheduled basis, whether the Agent is open or closed. You can also use the Agent graphic interface or command-line interface to initiate a backup.

For more information about file backup, refer to *Administering Agents* for your operating system.

The following figure shows the backup process:



Agents synchronize with the Data Center before and after a backup. During synchronization, the Agent receives configuration changes, messages, and upgrades, and it uploads Agent history logs.

File Management

This section describes how the Data Center handles files during backup.

Base and Delta Files

During the backup process, the Agent maintains a complete copy of the base file, and then captures the changes that occur between backups in delta files. The delta files are not complete pictures of the original file. They are only the changes to the file that occurred since last backup. After several backups, one file can accumulate many delta files, and reconstitution of that file for a retrieval request requires the Agent to get the baseline and all the accumulated deltas.

Expiration Dates

At some point, the original base file and some of its deltas expire. The expiration date depends on the expiration settings that you set for the Data Center. For example, some organizations, such as lawyers or medical offices, might turn off expiration dates for legal reasons.

Compactor, a Data Center service, searches the archives for expired files. Compactor evaluates each file. When Compactor determines that the base file or the base file and several delta files are expired, it creates a new baseline or rebases the file. For more information about Compactor, see [“Compaction” on page 45](#).

Rebasing

Rebasing combines the original base file and expired deltas to create a new base. Compactor must rebase a file before its expired base and deltas can be deleted. It extracts the base file and deltas from the archive or archives and rolls them up into a new file. After Compactor creates the new base file, it deletes the expired files and then repackages the remaining unexpired files into one or more new archives.

A new file is created and backed up from the account on March 17th (3/17). Subsequent modifications and backups occur over the next two days and then cease for that file.

archive1	base1	created and backed up on 3/17
archive2	delta1	modifications backed up on 3/18
archive3	delta2	modifications backed up on 3/19

The next time Compactor reviews this account, it rolls up the data in base1, delta1, and delta2 to create a new baseline, base2:

archive1	base1	expired on 5/17
archive2	delta1	expired on 5/18
archive3	delta2	expired on 5/19
archive6	base2	rolled up file created and archived on 5/31

Compaction

The compaction process removes data from the Data Center. To remove data, Compactor, a Data Center service, performs the following process:

1. Selects accounts.
2. Analyzes and repairs the system.
3. Marks files as expired.
4. Repackages archives.
5. Deletes expired archives and database entries.
6. Informs the Agent of changes.

These tasks represent a standard compaction cycle on a mirrored Data Center. For more information about each task, refer to *Administering the Data Center*. For more information about Compactor, see [“Compactor” on page 37](#).

CHAPTER 5

Connected Backup Deployment

This chapter describes, in general, the tasks that you must complete to deploy Connected Backup. The chapter presents the tasks in the order in which you must perform them.

- Deploy the Data Center
- Install Support Center and Account Management Website
- Use Support Center to Create Agent Communities
- Use Support Center to Create Agent Configurations
- Create Agent Rule Sets
- Deploy the Account Management Website
- Deploy Agents

Deploy the Data Center

If you want to host your Data Center, you must install the Data Center software. This section describes, in general, the tasks that you must perform to install the Data Center. For detailed information, refer to *Installing the Data Center*.

Prepare Your Environment

To prepare your environment

- Determine which Data Center configuration best suits your organization.

For information about types of Data Center configurations, see [“Data Center Configurations” on page 27](#).

- Determine which licensing option best suits your organization.

You must license every Data Center. You can purchase licenses for PC accounts, Mac accounts, or any combination of these accounts. Before you install the Data Center software, you must obtain a permanent license. However, if you do not have a license when you install a Data Center, the Data Center Setup program creates a temporary license that expires in 30 days.

Your Data Center license gives you access to optional features. Before you purchase your licenses, decide which features you want to use. The license software also tracks the number of active users and servers on the Data Center and warns you when your contracted license agreement nears capacity.

- Review the following requirements:
 - Data Center server requirements.
 - Storage solutions requirements.
 - Network requirements.
 - Security requirements for your Data Center.

For information about these requirements, refer to *Installing the Data Center*.

- Install and configure the required Microsoft software on the computer that will host the Data Center software.

The Data Center requires the following Microsoft software:

- Microsoft Windows Server
- Microsoft SQL Server

For a list of required software, refer to *Connected Backup Requirements Matrix*. For instructions about how to configure the software, refer to *Installing the Data Center*.

- Prepare the servers that will host Support Center and Account Management Website.

The tasks that you must perform to prepare servers to host Support Center and Account Management Website depend on your Data Center configuration. For more information, refer to *Installing the Data Center*.

Install and Enable MyRoam

MyRoam lets users retrieve backed-up files to computers that do not host the Agent. After users select the files that they want to retrieve, the Data Center creates a ZIP archive file that contains the selected files. Users download this file and extract it to their computer.

To use MyRoam, users must log on to the Account Management Website. For more information about how to install and enable MyRoam, refer to *Installing the Data Center*.

Gather Information that You Need to Provide During Installation

Before you install the Data Center software, complete the worksheets in Worksheets and Checklists in *Installing the Data Center*. Be sure to store the Data Center information in a secure location.

Install the Data Center Software

After you prepare your environment and install MyRoam, you can install the Data Center software. Use the information you recorded in “Appendix A: Worksheets and Checklists” in *Installing the Data Center*. As you perform the installation, complete “Appendix B: Data Center Installation Worksheets.”

The Data Center installation process creates a Master Encryption Key (MEK). Store this key in a safe place. You might need the MEK if you reinstall the Data Center software.

Back Up Certificate Files

After you install the Data Center, back up the certificate files that the software uses. Because these files do not change, you have to back them up only once. For a list of certificate files that you have to back up, refer to *Installing the Data Center*.

Verify the Data Center Installation

To make sure that the Data Center installation functions, verify the following components operate properly:

- BackupServer
- Mirror site replication (if you use a mirrored or clustered configuration)

For more information about how to verify the Data Center installation, refer to *Installing the Data Center*. The guide also contains information about how to troubleshoot problems with the installation.

Install Support Center and Account Management Website

Support Center is a Web-based management application that lets you create and manage Agent configurations and registered accounts.

Account Management Website is a Web-based application that allows users to perform the following tasks:

- Register a new Agent account and download the Agent software.
- View Agent account information.
- Modify profile information such as e-mail address and password.
- Recover an Agent account.
- Use the MyRoam application to retrieve files.
- For PC Agents, order images of backed-up files on different types of media.

You must install the Account Management Website component on a separate server from the Data Center.

Use Support Center to Create Agent Communities

A community is a group of Agent accounts that share common characteristics, such as configuration settings, the geographic location of the clients, or similar bandwidth throttling requirements. You can use communities to run reports, edit settings, upgrade Agent configurations, and manage accounts.

Each community that you create in Support Center appears as a node in the left pane of the Support Center interface. The node contains subnodes that represent the accounts, technicians, reports, configurations, and subcommunities in the community. You can create as many communities and subcommunities as necessary to organize your accounts.

For more information, refer to *Administering Agents* for your operating system. Also refer to Support Center Help.

Use Support Center to Create Agent Configurations

You create Agent configurations in Support Center to specify the features that are in the Agents that you deploy. An Agent configuration contains the following components:

Profile and Website settings	Determine the information and features that are available to users in the Account Management Website. They also determine the information that is in users' profiles, and the fields that are in the Agent Startup Wizard.
Components list	<p>Support Center compiles Agent configurations from a set of components that each specify some of the Agent's features. Agent configurations can contain the following components:</p> <ul style="list-style-type: none"> ■ Agent versions ■ Agent settings ■ Agent rule sets <p>For more information, refer to <i>Administering Agents</i> for your operating system. Also refer to <i>Support Center Help</i>.</p>
Default Agent configuration	<p>The Support Center installation creates a default Agent configuration (with a name similar to Default PC version Configuration or Default Mac version Configuration). The default configuration resides at the root level of the tree in Support Center and is available to all your communities. You might want to create your own configuration with a unique version, settings, and rules. However, you can use the default configuration as a reference when you create your own configurations.</p> <p>The default configurations contain the following components:</p> <ul style="list-style-type: none"> ■ Default Agent Version ■ Default Agent Settings ■ Default Agent Rule Sets ■ Default Agent Profile and Website Settings <p>For more information, refer to <i>Administering Agents</i> for your operating system. Also refer to <i>Support Center Help</i>.</p>

Create Agent Rule Sets

The Agent uses rules to determine which files to include or exclude from backups and recoveries. Rule types determine the order in which the Agent processes rules. For more information about rules, refer to *Administering Agents* for your operating system. Also refer to Support Center Help.

Deploy the Account Management Website

The Account Management Website lets users download Agent configurations, manage their account information, retrieve files (if you enable MyRoam), or, for PC Agents, order backed-up files on media such as CDs or DVDs when they work from a computer that does not host an Agent. For information about how to deploy the Account Management Website, refer to *Installing the Data Center*.

Deploy Agents

To deploy Agents, you or end users install them on client computers. Choose from the following installation methods:

- | | |
|--------------------------------------|---|
| User installation | Users register the Agent, and then download the Agent Setup file from the Account Management Website. The installation process prompts users for set up information. |
| Distributed user installation | Administrators download the Agent Setup file from Support Center and distribute it to users. The installation process prompts users for set up information. After users install the Agent, they must register it. If you enable the Agent Startup Wizard, the user experiences registration as a continuation of the installation process.

Use this type of installation when you want users who do not have access to the Account Management Website to install the Agent themselves. |

Disk image installation

Administrators install an inactive Agent that does not back up files until it is activated by a user. Install this type of Agent when you want only to include the Agent in a disk image of a computer that you want to clone to other computers.

After users receive a computer that has an inactive Agent, they must activate and register the Agent. If you enable the Agent Startup Wizard, the registration program runs the first time the user opens the Agent.

Hands-free installation

Administrators download the Agent Setup file from Support Center and use the installation command-line interface to install the Agent on multiple computers simultaneously without user participation.

For more information about the installation methods, refer to *Installing Agents* for your operating system.

Index

Symbols

- 32-bit support 17
- 64-bit support 17

A

- Account Management Website 35
 - definition of 23
- additional storage methods 27
- Agent Startup Wizard 18
- Agents
 - central upgrade 18
 - definition of 22
 - deploying 52
 - description 24
 - for disk images 17
 - selecting files for backup 24
 - types of 24
- architecture diagram 23
- archive storage devices
 - definition of 22
- archives
 - and expiration rules 44
 - sizing and splitting 34
 - splitting 34
- attributes 19

B

- backup
 - encrypted files 19
- backup server 25
- base files 24, 44
- branding 18

C

- cluster configurations 31
 - diagram 32
- communities
 - assigned server pair 33
 - on clustered Data Center 32
- compaction 45
- Compactor 45
 - description 37
 - expiring contents of archives 44
- components of Connected Backup 22
- compression 25
- configurations
 - cluster 31
 - mirrored 28
 - stand-alone 27
- Connected Backup
 - components 22
 - databases, definition of 22

D

- Data Center
 - archives 33
 - archives, lifecycle of 33
 - configurations 27
 - databases 26
 - definition of 22
 - load balancing 29
 - resynchronization 29
 - servers 25
 - toolkit 39
 - utilities 39
- databases 22, 26
 - directory 26

- registry 26
- replication of 26
- DataBundler, description 38
- delta files 24, 44
- deploying Agents 52
- diagrams
 - architecture 23
- digital signature 18
- Directory database 26
- disk image
 - Agent 17
 - installation 53
- distributed user installation 52

E

- e-mail backup 18
- EmailOptimizer 18
- encrypted files 19
- expiration of files 44

F

- features
 - Agent deployment options 17
 - Agent Startup Wizard 18
 - Agents for disk images 17
 - backup 16
 - branding 18
 - central upgrade for Agents 18
 - cross platform support 17
 - digitally signed installation program 18
 - e-mail backup 18
 - retrieve 17
 - support for encrypted files, metadata, attributes 19
 - support for transforms 17
- file management process 44
- files
 - backup process 41
 - base 44
 - delta 44
 - expiration 44

- expiration, and archives 44
- rebasing 44
- retrieval process 43

H

- hands-free installation 53

I

- installation
 - digitally signed 18
- installation options, Agents 52

K

- key features 16

L

- licensed product 16
- load balancing 29

M

- metadata 19
- mirrored configurations 28
 - definition of 27
 - diagram 30
- MyRoam 36
 - definition of 23

N

- network protocol used for backups 25

P

- processes
 - compaction 45
 - file backup 41
 - file retrieval 43
 - files
 - management 44

